

# LDX Optronics Inc.

## 900nm -1850nm Laser Diodes

Part Number	Wavelength (nm)	Output Power (mW)	Emitter Size (um)	Operating Temp (°C)	Threshold Current (mA) Typ.	Operating Current (mA) Typ.	Operating Voltage (V) Typ.	Beam Divergence		Spectral Width (FWHM)	Polarization
								θ// (°)	θ⊥ (°)		
LDX-3210-900	900 ±5 nm	2,000	100	20	200	2100	1.9	7	44	2	TE
LDX-3310-915	915 ±10 nm	3,000	100	20	250	2800	1.8	7	26	2	TE
LDX-3515-915	915 ±10 nm	5,000	150	20	400	5000	1.9	7	26	2	TE
LDX-3310-940	940 ±10 nm	3,000	100	20	250	2800	1.8	7	26	2	TE
LDX-3515-940	940 ±10 nm	5,000	150	20	400	5000	1.8	7	26	2	TE
LDX-3105-980	980 ±10 nm	1,500	50	20	200	1900	1.8	7	26	2	TE
LDX-3310-980	980 ±10 nm	3,000	100	20	250	2800	1.8	7	26	2	TE
LDX-3515-980	980 ±10 nm	5,000	150	20	400	5000	1.8	7	26	2	TE
LDX-3310-1064	1064 ±10 nm	3,000	100	20	300	3700	1.4	7	38	3	TE
LDX-3515-1064	1064 ±10 nm	5,000	150	20	500	7000	1.8	7	38	3	TE
LDX-3105-1120	1120 ±10 nm	1,200	50	20	250	2000	1.7	7	28	2	TE
LDX-3210-1120	1120 ±10 nm	2,500	100	20	300	4000	1.7	7	28	2	TE
LDX-3415-1120	1120 ±10 nm	4,000	150	20	450	6500	1.7	7	28	2	TE
LDX-3105-1210	1210 ±10 nm	1,200	50	20	250	2000	1.7	7	28	3	TE
LDX-3210-1210	1210 ±10 nm	2,000	100	20	300	4000	1.7	7	28	3	TE
LDX-3315-1210	1210 ±10 nm	3,000	150	20	450	6500	1.7	7	28	3	TE
LDX-3115-1350	1350 ±20 nm	1,500	150	20	900	7000	1.4	7	38	4	TE
LDX-3309-1470	1470 ±20 nm	3,000	95	20	500	7000	1.5	8	30	8	TE
LDX-3509-1470	1470 ±20 nm	5,000	95	20	500	9000	1.5	8	30	8	TE
LDX-3820-1470	1470 ±20 nm	8,000	200	20	800	18000	1.6	8	30	8	TE
LDX-3110-1550	1550 ±20 nm	1,200	100	20	800	5500	1.2	8	30	8	TE
LDX-3210-1550	1550 ±20 nm	2,000	100	20	800	9000	1.2	8	30	8	TE
LDX-3209-1550	1550 ±20 nm	2,500	95	20	500	6000	1.5	8	30	8	TE
LDX-3309-1550	1550 ±20 nm	3,500	95	20	500	9000	1.5	8	30	9	TE
LDX-2815-1620	1620 ±20 nm	800	150	20	900	5100	1.1	7	40	6	TE
LDX-3110-1850	1850 ±30 nm	1,000	100	20	400	5000	1.2	6	46	8	TE



The Standard Package is the C-mount. Other Packages are available at additional cost: D-mount, Q-mount, 9.0mm, 9.0mm Fiber coupled, TO-3 (no TEC), TO-3 (with TEC), HHL Free Space, HHL Fiber Coupled and CS Bar packages.

LDX follows a policy of continuous product improvement. **Specifications are subject to change without notice.**

These components do not comply with the Federal Regulations (21 CFR Subchapter 1) as administered by the Center for Devices and Radiological health. Purchaser acknowledges that his/her products must comply with these regulations before they can be sold to a customer.

**For Additional Information Contact:**



203 Joseph St. O'Fallon, Mo 63366  
 Phone: (636) 272-7227; fax (636) 272-3909  
 diodes@rpmclasers.com rpmclasers.com

5/27/2009



Copyright 2005. All rights reserved.